

## Switching Power Adaptor UES18LCP2-SPA Series

### Features

- ◆ AC input voltage range 90-264VAC
- ◆ Protections against: short circuit/over current/over voltage
- ◆ Energy efficiency level VI
- ◆ No Y design



Input Voltage Range	90-264VAC	Operation Temperature	-5~45°C
Input Current	0.5A	Storage Temperature	-40~70°C
Average Efficiency	Energy efficiency level VI	Humidity	5% to 95% non condensing
Output Voltage Tolerance	±5%	MTBF	100,000 hours at full load at 25°C ambient, calculated per MIL-HDBK-217
Standby Power	0.075W MAX		
Safety Standard	cULus(UL62368-1), CE(EN62368-1), PSE(J62368-1), RCM(AS/NZS62368.1), CB(IEC62368-1), FCC(Part 15)		
Weight	About105g	Dimensions	70mm (L) ; 30.2mm (W) ; 55mm (H)
Applications	ITE		

### Output data(UES18LCP2-SPA)



Model	Voltage (V)	Current (A)	Ripple (mV)	VI 115 230 (%)	Av. Eff. (%) Min
UES18LCP2-120YYYSAPA	12.0	0.01-1.50	200	Y Y	85.45

YYY:001-150 stands for current 0.01-1.50A  
CP-Changeable AC Plug

### Standard

EMC standard	EN55032/CISPR22; EN55024/CISPR24	
Conduction & Radiation	EN55032/CISPR22 Class B	
Harmonic Currents	IEC/EN 61000-3-2 Class A	
Voltage Flicker	IEC/EN 61000-3-3	
ESD	IEC/EN 61000-4-2 ±8KV Air, ±4KV Contact	
Radiated Immunity	IEC/EN 61000-4-3 3V/m	
EFT/Burst	IEC/EN 61000-4-4 ±1KV	
Surge	IEC/EN 61000-4-5 ±4KV DM, ±6KV CM	
Conducted Immunity	IEC/EN 61000-4-6 3Vrms	
Dips & Interruptions	IEC/EN 61000-4-11 0%, 70%, 0% of UT	