

Switching Power Adaptor UES15L2-SPA Series

Features

- ◆ AC input voltage range 90-264VAC
- ◆ Protections against: short circuit/over current/over voltage
- ◆ Meet 2KV surge immunity
- ◆ Energy efficiency level VI



Input Voltage Range	90-264VAC	Operating Temperature	-10~45 °C
Input Current	0.5A	Storage Temperature	-40~70 °C
Average Efficiency	Energy efficiency level VI	Operating Humidity	5% to 95% non condensing
Output Voltage Tolerance	±5%	MTBF	100,000 hours at full load at 25°C ambient, calculated per MIL-HDBK-217
Standby Power	0.1W MAX		
Safety Standard	Meet CB(IEC62368-1), CCC(GB4349.1),cULus(UL62368-1)		
Weight	About 82g	Dimensions	62.0mm (L); 29.0mm (W); 40.3mm (H)
Applications	ITE		

输出数据(UES15L2-SPAZ)

型号	电压 (V)	电流 (A)	纹波 (mV)	VI 115 230	平均效率 (%) Min
UES15L2-240YYYYSPAZ	24.0	0.01-0.60	240	Y Y	83.92

YYY:001-060 stands for current 0.01-0.60A

Z: U-AC Plug for US
 V-AC Plug for EU
 D-AC Plug for Brazil
 S-AC Plug for AU

Standard

EMC standard	EN55032/CISPR32;EN55035/CISPR35
Conduction & Radiation	EN55032/CISPR32 Class B
Harmonic Currents	IEC/EN 61000-3-2 Class A
Voltage Flicker	IEC/EN 61000-3-3
ESD	IEC/EN 61000-4-2 ±8KV Air, ±6KV Contact Class B
Radiated Immunity	IEC/EN 61000-4-3 3V/m Class B
EFT/Burst	IEC/EN 61000-4-4 ±1KV Class B
Surge	IEC/EN 61000-4-5 ±2KV DM, ±4KV CM
Conducted Immunity	IEC/EN 61000-4-6 3Vrms Class B
Dips & Interruptions	IEC/EN 61000-4-11 0%, 70%, 0% of UT