

# USB Charger UES65LZ4-SPC

## Features

- ◆ AC input voltage range 90-264VAC
- ◆ 2 Standard Type-C output ports; 1 standard USB-A output port  
It can fast charging two devices at the same time
- ◆ Protections against: short circuit/over current/over voltage/  
over temperature
- ◆ They are conveniently sized and portable for personal use  
anytime, anywhere
- ◆ Type-C Support PD3.0, PPS, QC3.0, QC2.0 Fast charging protocol
- ◆ USB-A Support QC3.0, QC2.0 Fast charging protocol
- ◆ When charging two devices simultaneously, intelligent  
power distribution enables each device to get optimal charging

GaN

NEW



Input Voltage Range	90-264VAC	Operating Temperature	-5~25°C
Input Current	1.5A	Storage Temperature	-40~80°C
Average Efficiency	Energy efficiency level VI	Operating Humidity	5% to 95% non condensing
Output Voltage Tolerance	±5%	MTBF	100,000 hours at full load at 25°C ambient, calculated per MIL-HDBK-217
Standby Power	0.3W MAX		
Safety Standard	CCC(GB4943.1), CB(IEC62368-1), CE(EN62368-1), FCC (Part 15)		
Weight	About 135g	Dimensions	74.0mm (L); 45.0mm (W); 33.5mm (H)
Applications	Notebook, Mobile phone, Game console, PDA and other charging devices		

## Output data (UES65LZ4-SPC)

CB © CE FC

### Output Port Combination

Type-C1/C2	5V/9V/12V/15V,3A; 20V/3.25A; 65W Max
USB-A	5V/3A,9V/2.22A,10V/2.25A,12V/1.67A; 22.5W Max
Type-C1+C2	45W+20W; 65W Max
Type-C1+A	45W+20W; 65W Max
Type-C2+A	5V/3A+5V/3A; 30W Max
Type-C1+C2+A	45W+5V/2A+5V/2A; 65W Max

Z: U-AC Plug for US & JP  
C-AC Plug for CN

## Standard

EMC standard	EN55032/CISPR32;EN55035/CISPR35
Conduction & Radiation	EN55032/CISPR32 Class B
Harmonic Currents	IEC/EN 61000-3-2 Class A
Voltage Flicker	IEC/EN 61000-3-3
ESD	IEC/EN 61000-4-2 ±8KV Air, ±4KV Contact Class B
Radiated Immunity	IEC/EN 61000-4-3 3V/m Class B
EFT/Burst	IEC/EN 61000-4-4 ±1KV Class B
Surge	IEC/EN 61000-4-5 ±1KV DM
Conducted Immunity	IEC/EN 61000-4-6 3Vrms Class B
Dips & Interruptions	IEC/EN 61000-4-11 0%, 70%, 0% of UT