


USB Charger UES30L-SPCC

Features

- ◆ AC input voltage range 100-240VAC
- ◆ Includes overcurrent protection and short-circuit protection
- ◆ Complies with China's Level 3 energy efficiency standard
- ◆ Output specifications: 5V/9V/15V/20V, maximum power 30W
- ◆ Suitable for operating altitudes up to 5000 m
- ◆ Comes with a 0.8 m data cable
- ◆ Type-C Support PD3.0 Fast charging protocol



Input Voltage Range	100-240VAC	Operating Temperature	0~35℃
Input Current	1.0A MAX	Storage Temperature	-20~60℃
Average Efficiency	China's Level 3 energy efficiency	Operating Humidity	5% to 90% non condensing
Output Voltage Tolerance	±5%	MTBF	100,000 hours at full load at 25℃ ambient, calculated per Telcordia_SR-332
Standby Power	0.1W MAX		
Safety Standard	CQC(GB4706.1),China Energy Efficiency(GB20943)		
Weight	85g	Dimensions	67.3mm (L); 30.2mm (W); 42.0mm (H)
Applications	Smartwatches, Bluetooth earphones, and Wireless mice		

Output data (UES30L-SPCC)

Output Port	Voltage (V)	Current (A)	Ripple (mV)	Av. Eff. (%) Min
Type-C	5.0	0.0-2.0	158	78.7%
	9.0	0.0-2.0	175	85.0%
	15.0	0.0-2.0	170	86.95%
	20.0	0.0-1.5	156	86.95%

Standard

EMC standard	EN55032/CISPR32;EN55035/CISPR35
Conduction & Radiation	EN55032/CISPR32 Class B
Harmonic Currents	IEC/EN 61000-3-2
Voltage Flicker	IEC/EN 61000-3-3
ESD	IEC/EN 61000-4-2 ±8KV Air, ±4KV Contact Class B
Radiated Immunity	IEC/EN 61000-4-3 3V/m Class B
EFT/Burst	IEC/EN 61000-4-4 ±1KV Class B
Conducted Immunity	IEC/EN 61000-4-6 3Vrms Class B
Dips & Interruptions	IEC/EN 61000-4-11 0%, 70%, 0% of UT